

Dlite® **vanera LED**
LIGHT IN UNDERSTATED ELEGANCE


LED VTL



Dlite® vanera LED

THE RIGHT CHOICE FOR THE ENERGY-CONSCIOUS.

The new vanera LED provides ideal lighting in the customary high vanera quality. The special wide-angle and anti-glare technology assures optimized low-glare and low-reflection light control. With its sleek silhouette, it integrates stylishly and harmoniously in any room. Even low and narrow corridors or door areas in residential rooms are homogeneously and uniformly illuminated. The direct and indirect lighting components give rooms a friendly and bright ambiance. NEW: optional available as version VTL.

Advantages at a glance:

- Quality LED module:
Energy demand reduced by approximately 25% as compared to T16 fluorescent light sources
- High-quality materials and processing:
durable side and front panels made of aluminum
- Sleek dimensions:
open up additional applications and design options

Technical details:

- Color rendering CRI>80
- Power consumption 40 W (at approximately 2700 lm)
60 W (at approximately 4100 lm)
80 W (at approximately 5100 lm)
- Ceiling and wall mounting
- Protection class IP20 / bathroom version IP44
- LED service life 50 000 hrs L90 / B10
70 000 hrs L70 / B10

Order numbers:

D15.390.00	vanera LED 80	924 x 105 x 45 mm
D15.391.00	vanera LED 60	924 x 105 x 45 mm
D15.392.00	vanera LED Bath 40	643 x 105 x 45 mm
D15.393.00	vanera LED 80 DALI version	924 x 105 x 45 mm
D15.394.00	vanera LED 60 DALI version	924 x 105 x 45 mm
D15.395.00	vanera LED 60 directly/indirectly individually switchable	924 x 105 x 45 mm
D15.396.00	vanera LED 80 directly/indirectly individually switchable	924 x 105 x 45 mm
D15.398.000	vanera LED VTL 60 C	924 x 105 x 45 mm
D15.397.000	vanera LED VTL 80 C	924 x 105 x 45 mm

